






Machine Dimensions and Weight



Cylinder Fixturing Options

Hollow Cylinder Direct Cones	Both Shafted and Hollow Inner/Outer Cones
--	---



Max Overall Shafted
 (A) —
Max Face Length
 (C) 1400 mm

Bore range
 Small cone: 60 - 110 mm
 Large cone: 80 - 125 mm


Max Overall Shafted
 (A) 1400 mm
Max Face Length
 (B) 1400 mm
 (C) 1400 mm

Bore Range (diameter)
 Outer 75 - 115 mm
Shaft diameter
 Inner 26 - 68 mm


Cylinder Data

Circumference range	350 - 1200 mm ⁽¹⁾
Weight maximum	500 kg
Allowable cylinder taper ⁽²⁾	75 µm
Allowable runout	50 µm
Copper hardness	190 to 230 HV
Deviation of copper hardness	+/-5 HV

Shafted Cylinders



Hollow Cylinders



(1) Maximum physical cylinder sizes. Engraveable Circumferences depend upon applied engrave head, engraving frequency, screen, and screen angle range.
 (2) See Site Survey 9800-3143 for machine weight and other details

Machine Technical Data

Environmental Temperature	20 - 25°C, 40-65% relative humidity, non-condensing	
Heat dissipation	1.5kW	
Floor bowing under load	0.2 mm/m	
	Execution according to DIN 18202	
	Do not use intermediate floors or support beams as machine foundation	
Maximum allowable floor vibration	Peak to Peak Amplitude	Frequency
	3.8 µm	2 - 8 Hz
	2.5 µm	9 - 15 Hz
	1.5 µm	16 - 21 Hz
	1.0 µm	>21 Hz

Connections

	Power	Voltage	FrequencyFuse
Power supply	5.00 kVA	1x220V +/- 3%	50/60Hz +/- 1%25A
	5.00 kVA	1x230V +/- 3%	50/60Hz +/- 1%25A
	5.00 kVA	1x240V +/- 3%	50/60Hz +/- 1%25A
Compressed Air	Minimum pressure of 586 Kilopascals or KPa (85 PSI). Minimum reserve capacity: 19 liters (5 gallons) per engraver. Only for Automated engraver		
Communication	Ethernet for Collage Interface. Internet connection, ideally via Collage computer, for TeamViewer remote support is strongly suggested		